



TS4-A-S

Module-level monitoring and rapid shutdown

The Tigo TS4-A-S improves production, safety, and intelligence in new designs and existing systems. Patented technology delivers top performance with high efficiency for a fast ROI. Easy installation and long-term reliability reduce system downtime and truck rolls, while Tigo’s Energy Intelligence platform enables quicker onsite commissioning and comprehensive remote monitoring.

Features

- Simple, fast installation – snaps to a standard PV module frame or mounts to racking
- Module-level monitoring – full visibility into module- and system-level production
- Rapid shutdown – a UL Standards-certified component for photovoltaic rapid shutdown systems (PVRSS) worldwide
- Works with any system – fully compatible with thousands of different inverter models from more than 50 inverter brands
- 25-year warranty
- Monitoring, rapid shutdown, and remote troubleshooting with Tigo Access Point (TAP) and Cloud Connect Advanced (CCA)

Specifications

Electrical

Maximum current (I_{MP}/I_{SC})	15 A/20 A
Input voltage range (V_{MP})	16 – 80 V (UL) 16 – 90 V (IEC)
Maximum input voltage	80 V (UL)/90 V (IEC)
Maximum system voltage (V_{MAX})	1000 V/1500 V*
Maximum output current (I_{MAX})	15 A
Maximum output power (P_{MAX})	700 W
Maximum fuse rating	25 A
Maximum efficiency	99.6%

AS 5033: Operational Output

Maximum output current	$I_{DCU MAX}$
Maximum output voltage	$V_{DCU MAX}$
Maximum output power	$P_{DCU MAX}$

Rapid Shutdown

TS4 conductor AWG	12
Rapid shutdown time limit	<30 sec.
PVRSE-controlled conductor limits	$\leq 240 VA, \leq 8 A, \leq 30 V_{DC}$
UL 1741-compliant PVRSE	Yes
Communications	Wireless

Connections

Input (from module) cable lengths	0.12/0.62 m
Output (to string) cable lengths	1.2/2 m
Connectors	MC4/EVO2

* Depending on UL/IEC certification



Specifications

Environmental

Operating temperature range*	-40 – 75 °C (-40 – 167 °F)
Storage temperature range	-40 – 85 °C (-40 – 185 °F)
Maximum elevation	2000 m (6560 ft.)
Outdoor IP rating	IP68/NEMA 3R

Mechanical

Dimensions (H/W/D)	139.7 x 138.4 x 22.9 mm (5.4 x 5.5 x 0.9 in.)
Weight	490 g (1.1 lb.)

General

Standards compliance	FCC 15b, ETSI EN 301 489, CISPR 31, CSA 22.2, IEC 62109, NEC 690.12 UL 1741 PVRSE/PVRSS
Warranty	25 years

* IEC rating: -40 – 85 °C (-22 – 185 °F)

Ordering Information

Part Number	V _{MAX} Certifications UL/IEC	Cable Lengths	Connectors
466-00252-20	1500 V/1000 V	1.2/2 m	MC4
466-00252-32	1500 V/1000 V	0.12/1.2 m	MC4
466-00252-62	1500 V/1000 V	0.62/1.2 m	MC4
466-00261-32	1500 V/1500 V	0.12/1.2 m	EVO2
466-00261-62	1500 V/1500 V	0.62/1.2 m	EVO2

More Resources

